





# WICK<sup>®</sup> XP<sup>D</sup> 2-14



## PORTABLE TWO STAGE HIGH PRESSURE FIRE PUMP

- Powered by an 14 HP, 4 stroke, Briggs and Stratton Vanguard air cooled engine with over-speed protection
- Electric start (battery optional) with manual recoil backup
- Cyclonic air cleaner
- Standard High inclination engine which can work at up to 45 degree angle.
- Two stage foam compatible pump end, interchangeable with our 4 stage pumps end pump end for increased pressure.
- Engine and pump are coupled with our stainless steel quick release clamp
- Maintenance-free speed increaser
- Choice of hand carrying tube frame, semi wraparound frame, or a channel base frame for vehicle mount
- Hand priming pump and pressure gauge included
- Standard with side port poppet check valve
- Optional Remote Fuel (RFT) connection
- For *value protection* the RFTV model comes standard with our *low pressure shut-off*

Performance standard correction as per SAE J1349; 60° F / 15.5° C; Baro 29.92 in. / 101.3 mB



### WEIGHT & DIMENSIONS

Length	33.0"	84 cm
Width	18.5"	47 cm
Height	19.0"	48 cm
Weight	126 lbs	57.2 kg
Suction	2.0" NPSH	50 mm
Discharge	1.5" NPSH	38 mm

### ENGINE

B&S Vanguard	4 stroke; 14 Hp @ 3600 RPM	
Oil filter	Cartridge-type spin-on filter	
Ignition	Electronic	
Fuel Tank Capacity	1.51 US Gal.	5.74 L

Specifications subject to change without notice

5838 Cypihot  
 Saint Laurent, QC  
 Canada, H4S 1Y5

Phone 514.335.4337  
 Phone 877.937.9660  
 Fax 514.335.9633

mercedestextiles.com  
 sales@mercedestextiles.com



# WICK XP2-14

## BID SPECIFICATION

- The pump must be powered by a Briggs & Stratton, 14 HP, Vanguard, 4 Stroke air-cooled engine
- The engine must be electric start with optional battery and have a manual recoil backup
- Must come standard with High Inclination engine which can work at up to 45 degree angle.
- It must have an interchangeable two stage foam compatible pump end. The two stage pump end must also be interchangeable with four stage pump ends for increased pressure.
- Must have a speed increaser that is a one-piece housing and that features a maintenance free belt/pulley design. Split belt housings are not acceptable and do not meet this specification.
- Must enable the drive belt to be checked without removing the pump or pump flange. Split belt housings that require disassembly are not acceptable and do not meet this specification.
- The pump end must attach to the speed increaser by the use of a one-piece stainless steel pump-mounting clamp. The clamp must also be fitted with a safety lock. Multi-part clamps do not meet this specification.
- Must include a non-return side port discharge poppet check valve. Units with flapper check valves are not acceptable and do not meet this specification.
- Must include a liquid filled gauge with a minimum range of 0-600 PSI / 0-40 Bar
- Must include a built in manual priming system. Units that require piping to be threaded into the pump end, are not acceptable and do not meet this specification. Units, that require attaching the primer, manually, to the discharge of the pump, in place of the hose, are not acceptable and do not meet this specification.
- Must come equipped with a full edge surround, anti-tip, low profile frame to permit easy handling or a channel mount frame. Narrow high profile frames which do not protect the pump and are unstable are not acceptable and do not meet this specification.
- Must be standard with integral fuel tank and available with remote fuel tank connection.
- Must be available with low pressure shutoff
- The pump must have minimum flow and pressures as shown in the performance chart on the opposite page



OPTIONAL  
FOUR STAGE PUMP END



# WICK XP2-14

Part#	Description
71WICKF200-14BC	WICK® XP2-14 Pumper ..14 HP 4 Stroke Briggs & Stratton , 2 stage pump, Channel frame model for vehicle mount
71WICKF200-14BT	WICK® XP2-14 Pumper ..14 HP 4 Stroke Briggs & Stratton , 2 stage pump, semi wraparound frame for easy transportation
71WICKF200-14BCH	WICK® XP2-14 Pumper ..14 HP 4 Stroke Briggs & Stratton , 2 stage pump, Horizontal Speed increaser model with channel frame



## OPTIONAL

	Part#	Description
A	71W42-2715	Large Control Panel
B	70FLPFTXX	Fuel Tank .. see website for complete listing
C	70FLPFL-XX	Fuel line .. see website for complete listing
D	70FL15TPPS	Thread protector 1 1/2" / 38mm
D	70FL20TPPS	Thread protector 2" / 51mm
E	70FL20DLPST0	Draftlite HP suction hose .. 2"/51mm x 10'/3M c/w NPSH *
F	70FLFV2PF	Foot Valve / Strainer 2"/51mm NPSH Female *

\* See website for complete listing of accessory and related products